

Amendments to Claims

1. (Currently Amended) A composition comprising:
a.) about 55 to about 75 weight percent trans-1,2-dichloroethylene; and

b.) about 15 weight percent or less of at least one solvent selected from the group consisting of:

i.) oxygen-containing solvents selected from the group consisting of alcohols, ketones, esters, siloxanes, and ethers; and

ii.) hydrocarbon solvents selected from the group consisting of those represented by C_tH_{2t+2} and C_tH_{2t} , wherein t is from 4 to 12; and

c.) about 20 to about 45 weight percent of at least one

i.) hydrofluorocarbon inerting agents selected from the group consisting of those represented by the formula $C_xH_yF_{(2x+2-y)}$, wherein x is from 3 to 8, y is from 1 to 4, the mole ratio of F/H in the hydrofluorocarbon inerting agent is greater than 1.6, and wherein when the inerting agent is hydrofluorocarbon the weight ratio of hydrofluorocarbon inerting agent to solvent is at least about 1.5;

ii.) hydrochlorofluorocarbon inerting agents selected from the group consisting of those represented by the formulae $C_2HCl_2F_{3-7}$ and C_2HClF_4 , and $C_3HCl_2F_{5-7}$, and wherein when the inerting agent is hydrochlorofluorocarbon the weight ratio of hydrochlorofluorocarbon inerting agent to solvent is at least about 2,

wherein said composition is non-flammable by Flame Extension Test ASTM D-3065 and Flash Point-Tag Closed Cup Test ASTM D-56-82, and said composition has a Kauri Butanol value of at least about 40 by ASTM 1133-94.

2. (Original) The composition of Claim 1, wherein said composition has a Kauri Butanol value of at least about 100 by ASTM 1133-94.

3. (Original) The composition of Claims 1 or 2, wherein the ratio of (inerting agent evaporation index)/(solvent evaporation index) is from about 0.1 to about 100.

4. (Original) The composition of Claims 1 or 2 wherein said oxygen-containing solvent is selected from the group consisting of alcohols having a normal boiling point greater than about 60°C and less than about 120°C, and represented by the formula $C_uH_{2u+1}OH$, wherein u is from 1 to 4; ketones having a normal boiling point greater than about 50°C and less than about 110°C, and represented by the formula $C_vH_{2v+1}COC_wH_{2w+1}$, wherein v and w are 1 or greater and v+w is at most 5; esters having a normal boiling point greater than about 55°C and less than about 130°C, and represented by the formula $C_kH_{2k+1}COOC_mH_{2m+1}$, wherein k and m are 1 or greater and k+m is at most 4; siloxanes, hexamethyldisiloxane ($[(CH_3)_3Si]_2O$), hexaethyldisiloxane ($[(C_2H_5)_3Si]_2O$), and octamethyltrisiloxane ($(CH_3)_3SiOSi(CH_3)_2OSi(CH_3)_3$); and ethylene glycol dialkyl ethers represented by the formula $C_aH_{2a+1}(OCH_2CH_2)_bOC_aH_{2a+1}$, wherein a is 1 to 3 and b is 1 to 6.

5. (Original) The composition of Claims 1 or 2 wherein said hydrocarbon solvent has a normal boiling point greater than about -15°C and less than about 130°C.

6. (Original) The composition of Claims 1 or 2 wherein said hydrofluorocarbon inerting agent is selected from the group consisting of $CF_3CHF_2CF_3$ (HFC-227ea), $CF_3CF_2CF_2H$ (HFC-227ca), $CF_3CH_2CF_3$ (HFC-236fa), $CF_3CHF_2CF_2H$ (HFC-236ea), $CF_2HCF_2CF_2H$ (HFC-236ca),

$\text{CF}_3\text{CF}_2\text{CFH}_2$ (HFC-236cb), $\text{CH}_2\text{FCF}_2\text{CHF}_2$ (HFC-245ca), $\text{CHF}_2\text{CHFCHF}_2$ (HFC-245ea), $\text{CH}_2\text{FCHF}_2\text{CF}_3$ (HFC-245eb), $\text{CHF}_2\text{CH}_2\text{CF}_3$ (HFC-245fa), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-329p), $\text{CF}_3\text{CF}_2\text{CFHCF}_3$ (HFC-329me), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CFH}_2$ (HFC-338q), $\text{CF}_3\text{CF}_2\text{CH}_2\text{CF}_3$ (HFC-338mf), $\text{CF}_3\text{CF}_2\text{CFHCF}_2\text{H}$ (HFC-338pe), $\text{CF}_3\text{CFHCF}_2\text{CF}_2\text{H}$ (HFC-338pce), $\text{CHF}_2\text{CF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-338pcc), $\text{CF}_3\text{CFHCFHCF}_3$ (HFC-338mee), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-42-11p), $\text{CF}_3\text{CF}_2\text{CFHCF}_2\text{CF}_3$ (HFC-42-11mce), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CFHCF}_3$ (HFC-42-11me), $\text{CF}_3\text{CF}_2\text{CH}_2\text{CF}_2\text{CF}_3$ (HFC-43-10mcf), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CH}_2\text{CF}_3$ (HFC-43-10mf), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CF}_2\text{CFH}_2$ (HFC-43-10q), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CFHCF}_2\text{H}$ (HFC-43-10pe), $\text{CF}_3\text{CF}_2\text{CFHCF}_2\text{CF}_2\text{H}$ (HFC-43-10pce), $\text{CF}_3\text{CHFCHFCF}_2\text{CF}_3$ (HFC-43-10mee), $\text{CF}_2\text{HCF}_2\text{CF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-43-10pccc), $\text{CF}_3\text{CFHCF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-43-10pcce), $\text{CF}_3\text{CFHCF}_2\text{CFHCF}_3$ (HFC-43-10mece), and $\text{CF}_3\text{CF}_2\text{CF}_2\text{CF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-52-13p).

7. (Canceled)

8. (Canceled)

9. (Original) The composition of Claims 1 or 2 wherein said inerting agent comprises $\text{CF}_3\text{CHFCHFCF}_2\text{CF}_3$ (HFC-43-10mee), and said solvent comprises ethanol.

10. (Original) The composition of Claim 9 comprising about 63 weight% trans-1,2-dichloroethylene, about 13 weight% ethanol, and about 24 weight% $\text{CF}_3\text{CHFCHFCF}_2\text{CF}_3$ (HFC-43-10mee).

11. (Original) The composition of Claims 1 or 2 further comprising at least one aerosol propellant selected from the group consisting of air, nitrogen, carbon dioxide, difluoromethane, trifluoromethane, difluoroethane, trifluoroethane, and tetrafluoroethane.

12. (Withdrawn) A process for removing residue from a surface, comprising the steps of:

a.) contacting the surface with the composition of Claims 1, 2, 9, 10 or 11; and

b.) recovering the surface substantially free of residue.

13. (Withdrawn) The process of Claim 12, wherein the surface comprises an integrated circuit device, and the residue comprises soldering flux.

14. (Withdrawn) The process of Claim 12, wherein the surface comprises an interior surface of a compression refrigeration apparatus, and the residue comprises conventional refrigeration lubricant, particulates, and/or rust.

15. (Currently Amended) The composition of Claims 1 or 2 further comprising a mold release agent.

16. (Currently Amended) A process for depositing mold release agent on the surface of a mold, comprising:

a.) contacting the surface of the mold with the composition of Claim ~~13~~15; and

b.) evaporating the components of said composition, with the exception of the mold release agent, from the surface of the mold.

Respectfully submitted,



CHYRREA J. SEBREE

Attorney for Applicants

Registration No.: 45,348

Telephone: (302) 992-3407

Facsimile: (302) 892-7925

Dated: March 23, 2004